

uniq tablet II

Rugged 12,2" industrial tablet

Intel® Kabylake m3-6Y30 (5G)



Windows



IP65



GPS



High-capacity



Bluetooth



1D



2D



RFID



4G/5G



WIFI

Functions

- Support for Windows 10 system
- Integrated 4G/5G all network communication, WiFi, Bluetooth and other communication modes
- 6300mAh, 1000mAh capacity dual battery, machine endurance 6-8 hours
- IP65 high protection level, in accordance with MIL-STD-810G
- Support GPS, more accurate positioning
- Support 1920x1200 FHD high score screen, optional with Corning gorilla TP and sunshine visual screen
- Support 1D/2D, NFC and other functional modules for free selection

Specification Parameter

Basic parameters

Dimension	319.6 x 216 x 23.4mm
Weight	Device unit 1500g
Device Color	Black
LCD	2.2 inch IPS 16:10, 1920*1200
Touch Panel	10points Capacitive, G+G, Corning Gorilla Glass
Camera	Front 2.0MP Rear 5.0MP
I/O	Type C x 1, USB 2.0 x 2, USB 3.0 x 1, SIM Card x 1, TF Card x 1, HDMI 1.4a x 1, 12pins Pogo Pin x 1, RS232 x 1, RS485 x 1, RJ45 (10/100M) x 1, Φ 3.5mm standard earphone jack x 1, Φ 3.5mm DC jack x 1
Power	AC100V ~ 240V, 50Hz/60Hz output DC 12V/4A
GPS	Support GPS

Optional modules

NFC	Support ISO/IEC 14443A/14443B/15693/ 18092/MIFARE protocol, Card reading distance: 4cm
1D	MOTO SE655E100R, Optical Position: 5mil, Scan speed: 50 times/s
2D	Honeywell N3680, Optical Position: 5mil, Scan speed: 50 times/s

Performance parameter

CPU	Intel® Kabylake m3-6Y30
OS	Windows 10
RAM	4GB/8GB LPDDR3
ROM	128GB/256GB/512GB

Battery

Capacity	6300mAh/7.4V, 1000mAh/7.4V
Type	Built in dual polymer lithium ion battery
Endurance	6hrs(default 50% volumn, default 200 lumens brightness, play 1080P HD video)

Network connections

WIFI	2.4G+5.8G dual frequency, WIFI 802.11(a/b/g/n/ac)
Bluetooth	BT4.2 (BLE) class1 transmission distance: 10m
4G/5G	LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B9/B12/B13/B14/B17/B18/B19/B20/B25/B26/B28/B29/B30/B32/B66/B71 LTE-TDD: B34/B38/39/B40/B41/B42/B48 5G: n1/n2/n3/n5/n7/n8/n12/n20/n28/n38/n40/n41/n48/n66/n71/n77/n78/n79

Reliability

Operate Temperature	-10 °C ~ 50 °C
Store Temperature	-20 °C ~ 60 °C
Humidity	95% Non-Condensing
IP Grade	IP65

Product Six Views

